




Ductile Caster for Heavy Loads

TBR



unit:mm

Wheel diameter	Type	Material	Load capacity	Total Height	Bolt hole spacing	Plate dimension	Hub length	Offset	Bolt hole diameter	Axle bore diameter
100	100×50TBR B	Rubber (with bearing)	140kg	145	104×104	136×136	69	40	11	17
	100×65TBR B		180kg				80			
	100×50TBR ULB	Urethane (with bearing)	340kg				69			
125	125×50TBR B	Rubber (with bearing)	180kg	178.5	110×110	142×142	69	45	11	25
	125×65TBR B		220kg				80			
	125×50TBR ULB	Urethane (with bearing)	400kg				69			
	125×50TBR FB	Metal (with bearing)	400kg				69			
	125×65TBR FB		470kg				80			
	150	150×50TBR B	Rubber (with bearing)				210kg			
150×65TBR B		250kg		80						
150×75TBR B		310kg		94						
150×50TBR ULB		Urethane (with bearing)	440kg	69						
150×65TBR ULB		590kg	80							
150×75TBR ULB		720kg	94							
150×50TBR FB		Metal (with bearing)	440kg	69						
150×65TBR FB			590kg	80						
150×75TBR FB			720kg	94						
180			180×50TBR B	Rubber (with bearing)	250kg	235	125×125	161×161	69	55
	180×65TBR B	280kg	80							
	180×75TBR B	350kg	94							
200	200×50TBR B	Rubber (with bearing)	280kg	260	136×136	172×172	69	60	14	25
	200×65TBR B		320kg				80			
	200×75TBR B		380kg				94			
	200×90TBR B		510kg				104			
	200×50TBR ULB	Urethane (with bearing)	650kg				69			
	200×65TBR ULB		720kg				80			
	200×75TBR ULB		880kg				94			
	200×90TBR ULB		1000kg				104			
	200×75TBR FB	Metal (with bearing)	880kg				94			
	250	250×65TBR B	Rubber (with bearing)				400kg			
250×75TBR B		470kg		94						
250×90TBR B		580kg		105						
250×65TBR ULB		Urethane (with bearing)	900kg	80						
250×75TBR ULB			1070kg	94						
250×90TBR ULB			1270kg	105						
250×65TBR FB		Metal (with bearing)	900kg	80						
250×75TBR FB			1070kg	94						
300			300×75TBR B	Rubber (with bearing)	540kg	365	170×170	210×210	94	16
	300×90TBR B	620kg	105							
	300×100TBR B	900kg	360		212×212	120				
	300×75TBR ULB	Urethane (with bearing)	1210kg	365		210×210		94		
	300×90TBR ULB		1450kg		105					
	300×100TBR ULB		1610kg	360	212×212	120				
	300×75TBR FB	Metal (with bearing)	1210kg	365		210×210		94		